



.....
SAKRETE CONCRETE & MORTAR REPAIR
.....

SAKRETE Concrete & Mortar Repair is a siliconized, acrylic-latex, repair product used to create flexible, durable seals around concrete surfaces. Repair cracks in concrete walks, driveways, foundations, steps, blocks or mortar joints. Weather-resistant after curing. Not for use in areas of prolonged contact with water. Cracks or joints should be approximately 3.2 mm (1/8") to 10 mm (3/8") in width.

FEATURES & BENEFITS

- For vertical and horizontal surfaces
- Protect against damaging freeze-thaw cycles
- Flexible and durable
- Ready-to-use
- Fast-drying

READ ALL DIRECTIONS BEFORE STARTING WORK.
ATTENTION: WEAR GLOVES, SAFETY GLASSES AND PROTECTIVE CLOTHING!

PROCEDURES

Surface and sealant must be above 10 °C (50 °F) and remain so for 48 to 72 hours for proper curing. Temperature and relative humidity will affect curing time.

Surface Preparation: Clean all surfaces before application. Cleaned surfaces may be moist. Cracks or joints should be approximately 3.2 mm (1/8") to 10 mm (3/8") in width. Fill deep cracks with backer rod to within 10 mm (3/8") of surface. Very small cracks should be slightly widened to permit penetration of caulking.

Application: Cut tube nozzle to desired bead width and squeeze caulking material into crack using standard caulking gun. Smooth and trim off excess with moist putty knife or jointing tool while material is fresh.

CURING

Allow to air-cure for 48 to 72 hours prior to traffic.

CLEAN UP

Cleans up with water prior to drying.

YIELD

300 mL (10.1 oz) tube fills a space approximately:
6 mm (1/4") x 6 mm (1/4") x 7.6 m (25').

PACKAGING

300 mL (10.1 oz) tube

UPC

764661195115

STORAGE & SHELF LIFE

Protect from freezing. Store between 1.7 °C (35 °F) and 37.7 °C (100 °F). Unopened container has a shelf life of 12 months.

SAFETY PROCEDURES

Do not swallow. Do not get in eyes or on skin. KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

EYES: Flush thoroughly with water for 15 minutes and seek medical attention.

SKIN: Wash off with soap and water.

For emergency information call CHEMTREC at 800-424-9300.

WEBSITE

For more information and other projects, visit us at www.sakretecanada.com or call us at 866-725-7383.



.....
SAKRETE CONCRETE & MORTAR REPAIR
.....

Warranty: This product is designed to meet the performance specifications outlined in this product data sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade. [REV.0004_07/18/19]

KING PACKAGED MATERIALS COMPANY
.....

Oakville Office
555 Michigan Dr.,
Oakville, ON
L6L 0G4

Montreal Office
3825 rue Alfred-Laliberté,
Boisbriand, QC
J7H 1P7

Brantford Office
541 Oak Park Rd.,
Brantford, ON
N3T 5L8

Sudbury Office
644 Simmons Rd.,
Dowling, ON
P0M 1R0