



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

### SECTION 1. IDENTIFICATION

Product name : Sakrete Asphalt Repair

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 2

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 1 (Lungs)

Specific target organ toxicity - repeated exposure : Category 2 (thymus, Liver, Bone marrow)

#### GHS label elements



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H350 May cause cancer by inhalation.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.  
H373 May cause damage to organs (thymus, Liver, Bone marrow) through prolonged or repeated exposure.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
calcium oxide	1305-78-8	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	$\geq 10 - < 30$
Quartz RCS (respirable crystalline silica)	14808-60-7	STOT RE 1; H372 Carc. 1A; H350i STOT SE 3; H335	$\geq 5 - < 10$
Asphalt	8052-42-4	Carc. 2; H351	$\geq 5 - < 10$
manganese oxide	1344-43-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	$\geq 5 - < 10$
Diesel	68476-30-2	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Carc. 2; H351 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 5 - < 10$

Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer by inhalation.  
Suspected of causing cancer.  
Causes damage to organs through prolonged or repeated exposure.  
Excessive lachrymation  
Erythema  
Dermatitis
- Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Use personal protective equipment.  
Deny access to unprotected persons.



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

gency procedures

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA	2 mg/m3	CA AB OEL
			2 mg/m3	CA BC OEL
		TWAEV	2 mg/m3	CA QC OEL
			2 mg/m3	ACGIH
Diiron trioxide	1309-37-1	TWA (Respirable)	5 mg/m3	CA AB OEL
			5 mg/m3 (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
			10 mg/m3	CA BC OEL



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

		(Fumes)	(Iron)	
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
silica, vitreous	60676-86-0	TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWA (Respirable particulates)	0.025 mg/m3 (Silica)	CA AB OEL
magnesium oxide	1309-48-4	TWA (Fumes)	10 mg/m3	CA AB OEL
		TWA (Inhalable fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWA (Respirable dust and fume)	3 mg/m3 (Magnesium)	CA BC OEL
		STEL (Respirable dust and fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWAEV (inhalable dust)	10 mg/m3	CA QC OEL
aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWA (Respirable)	1 mg/m3 (Aluminum)	CA BC OEL
		TWAEV (respirable aerosol fraction)	5 mg/m3	CA QC OEL
		TWAEV (inhalable dust)	10 mg/m3	CA QC OEL
		TWAEV (respirable aerosol fraction)	3 mg/m3	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
Quartz RCS (respirable crystalline silica)	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWA (Res-	0.025 mg/m3	CA BC OEL



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

		pirable)	(Silica)	
		TWAEV (respirable aerosol frac- tion)	0.05 mg/m3	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m3	CA BC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
Asphalt	8052-42-4	TWA (Fumes)	5 mg/m3	CA AB OEL
		TWA (Inhal- able fume)	0.5 mg/m3 (benzene soluble aerosol)	CA BC OEL
		TWAEV (Fumes)	5 mg/m3	CA QC OEL
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
manganese oxide	1344-43-0	TWAEV (in- halable dust)	0.2 mg/m3 (Manganese)	CA QC OEL
Diesel	68476-30-2	TWA	100 mg/m3 (total hydrocar- bons)	CA AB OEL
		TWA (Va- pour and inhalable aerosols)	100 mg/m3 (total hydrocar- bons)	CA BC OEL
		TWA (Inhal- able fraction and vapor)	100 mg/m3 (total hydrocar- bons)	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
 Wash hands before breaks and immediately after handling the product.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Wash thoroughly after handling.  
 Avoid breathing dust.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : solid

Color : black



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

Odor	:	solvent
Odor Threshold	:	No data available
pH	:	No data available
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 93 °C (> 199 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified due to lack of data.

##### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

May cause cancer by inhalation.

Suspected of causing cancer.

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Quartz RCS (respirable crystalline silica) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans	
<b>OSHA</b>	Asphalt (Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving)	8052-42-4
	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
<b>OSHA</b>	OSHA specifically regulated carcinogen	
	Quartz RCS (respirable crystalline silica)	14808-60-7



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

(crystalline silica)

<b>NTP</b>	Known to be human carcinogen Quartz RCS (respirable crystalline silica) (Silica, Crystalline (Respirable Size))	14808-60-7
------------	---	------------

### Reproductive toxicity

Not classified due to lack of data.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
May cause damage to organs (thymus, Liver, Bone marrow) through prolonged or repeated exposure.  
Prolonged exposure can cause silicosis.

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

---

### SECTION 15. REGULATORY INFORMATION

#### Canadian lists

No substances are subject to a Significant New Activity Notification.

No substances are subject to CEPA Section 84 Ministerial Conditions.

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current



## Sakrete Asphalt Repair

Revision Date 08/21/2025

Print Date 08/21/2025

Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date : 08/21/2025  
Date format : mm/dd/yyyy

Person who prepared the SDS : R & D of Sika Canada Inc.

Material number : 645,816

CA / Z8