

SAKRETE CONCRETE CRACK FILLER

SAKRETE Concrete Crack Filler is a high grade, pourable crack filler for concrete surfaces. Ready to use, flowable, polymer repair material designed to fill and seal cracks in concrete up to 13 mm (1/2") wide x 6 mm (1/4") deep.

FEATURES & BENEFITS

- Flexible, durable material
- Protect concrete surfaces against damaging freeze-thaw cycles
- Ready-to-use

USFS

Ideal for cracks in concrete driveways, patios and walkways.

READ ALL DIRECTIONS BEFORE STARTING WORK. ATTENTION: WEAR GLOVES, SAFETY GLASSES AND PROTECTIVE CLOTHING!

PROCEDURES

Do not apply when temperatures are expected to fall below 10 $^{\circ}$ C (50 $^{\circ}$ F) within 24 hours.

Surface Preparation: Clean area and remove all loose concrete, grease, oil, paint, dirt and any foreign materials that will inhibit performance.

Mixing: Shake vigorously before using.

Placement: Cut applicator tip to size needed for repair. Squeeze SAKRETE Concrete Crack Filler into cracks. Troweling is not necessary. Deep cracks may require more than one application due to shrinkage during curing and will have extended drying times. Allow to dry overnight between applications. Maximum crack width of 13 mm (1/2"), and maximum depth of 6 mm (1/4"). Width to depth ratio should be 2 to 1.

CURING

Protect from rain and water for 24 hours. DO NOT apply any portland cement-based products over top of the crack filler.

YIFI D

0.95 L (1 qt) bottle will fill a crack approximately: 10.6 m (35 ft) x 6 mm (1/4") x 13 mm (1/2").

PACKAGING UPC

0.95 L (1 qt) bottle 764661193166

STORAGE & SHELF LIFE

Store in tightly closed original container. KEEP FROM FREEZING. Unopened package has a shelf life of 12 months.

SAFETY PROCEDURES

Wear protective clothing and equipment. WARNING! Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin.

FIRST AID TREATMENT: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention.

WEBSITE

For more information and other projects, visit us at www.sakretecanada.com or call us at 866-725-7383.



SAKRETE CONCRETE CRACK FILLER	

Warranty: This product is designed to meet the performance specifications outlined in this product data sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade. [REV.0005_07/18/19]